



Enecon North East News
Apr. 2015 | Vol 7. Issue 4



Metalclad CeramAlloy CL+AC



Volume 7 Issue 3
Nitrogen Plant Uses
ENECON Epoxy Floor
System



Volume 7 Issue 2
Nuclear Circ Pump
Casing Protected with
ENECON

Check Out Our New
Products

Universal Hinge
www.universalthinge.com



Tube Cleaning
Equipment
www.elliott-tool.com/die-hard/



Waste Gas Cleaning Plant Exhaust Stack Protected with CeramAlloy

Waste gas from the steel making process is treated at this waste gas cleaning plant. A new steel exhaust stack was being installed and the plant's engineers wanted to protect the 90 degree bend in the stack (also known as the "lobster back") from the extremely corrosive environment.

The 10 segments of the lobster back were grit blasted to a 75-100 micron (3-4 mil) profile. A mineral based blast media was first used to achieve the necessary level of cleanliness followed by an angular steel grit to achieve the necessary profile. This profile was extremely important to insure maximum adhesion as the temperature of this equipment operates up to 200° C (302° F) in this aggressive chemical environment.

Immediately after blasting, the first 2 layers of CeramAlloy CL+AC were spray applied using hopper guns. A third layer was then applied by roller and brush.

Overall, approximately 700 kg of CeramAlloy CL+AC were used and all 10 segments were completed on-time and on-budget.



**CONTACT US TODAY TO LEARN MORE ABOUT OUR
UNIQUE PRODUCTS AND SPECIALIZED PROJECT SERVICES**

58 Florida Street, Farmingdale, NY 11735
Telephone: 631-414-7818
Fax 631-414-7822
Email: solutions@eneconaps.com
Website: www.eneconaps.com

ENECON[®] NORTH EAST APPLIED POLYMER SYSTEMS

We Solve Your Toughest Fluid Flow Repair and Maintenance Problems

© Copyright 2015 ENECON® Northeast